

NIGHTINGALE SUPPLY

PO BOX 712 HAMILTON CENTRAL QLD 4007
PHONE: (07) 3260.6544 FAX: (07) 3260.6646
EMAIL: nightingale1@hotmail.net.au

TECHNICAL DATA SHEET

GRASP:96 SC (G)

Polystyrene Contact Adhesive

➤ DESCRIPTION

Is a synthetic rubber based adhesive suitable for bonding Polystyrene and Polystyrene expanded foam to vinyl, linoleum, cork, rubber, wood, fibreboard, masonite, iron and concrete. It should preferably be applied by spray.

➤ TYPICAL PROPERTIES:

| | |
|-------------------|--------------------------|
| Appearance: | Green |
| Viscosity: | 600 - 1000 cps (4/20/25) |
| Solids : | Approximately 32% |
| Specific Gravity: | Approximately 0.80% |

➤ DIRECTIONS FOR USE:

To obtain best results, the surface must be dry and free from grease, dust and other contaminants. Leather and Rubber must be thoroughly roughened, stir well before use. Porous surfaces must be primed with a diluted version of Grasp 96SC IE Thinned with Grasp 96SC solvent followed by normal applications.

SPREAD RATES: 4-6 square metres per Litre applied by using a spray or brush.

OPEN TIME: 15-30 minutes

PRESSING SCHEDULE: Approx. 4 bar (4 kg/sq cm) for 10-15 seconds.

➤ CLEAN UP:

Use Grasp 96SC solvent. If working with polystyrene, otherwise Grasp Thinners AT.

➤ STORAGE & HANDLING:

Grasp 96SC contains flammable solvents with a flash point below 21C.

Avoid smoking and open flames. Is toxic by inhalation Provide good ventilation during work.

Avoid contact with skin and eyes. Keep out of reach of Children.

➤ PACKAGING: 4 Ltr, 20 Ltr, 200 Ltr

The information presented is believed to be accurate, however, no guarantee is implied or given. User should conduct their own testing to determine the suitability of any product for a particular purpose.