

# NIGHTINGALE SUPPLY

PO BOX 712 HAMILTON CENTRAL QLD 4007  
PHONE: (07) 3260.6544 FAX: (07) 3260.6646  
EMAIL: nightingale1@hotmail.net.au

## TECHNICAL DATA SHEET

# GRASP:96 SC (PS)

### PRESSURE SENSITIVE ADHESIVE

➤ **USES and ADVANTAGES:**

For bonding polystyrene to itself or to vinyl, linoleum, cork, rubber, wood, fibreboard, masonite, iron and concrete.

It is ideal for spray applications. Can be applied by brush or roller. May be used as a contact adhesive or pressure sensitive adhesive.

➤ **TYPICAL PROPERTIES:**

Appearance:	Thin blue liquid.
Viscosity:	600 - 1000 cps (4/20/25)
Solids :	Approximately 32%
Specific Gravity:	Approximately 0.80%
Flammability:	Flash point below 21°C
Open time:	15 – 30 minutes.
Storage:	18 months

➤ **DIRECTIONS FOR USE:**

To obtain best results, the surface must be dry and free from grease, dust and other contaminants. Porous surfaces must be primed with a diluted version of Grasp 96SC (PS). IE Thinned with Grasp 96SC (PS) solvent followed by normal applications.

SPREAD RATES: 4-6 square metres per Litre applied by using a spray or brush.

OPEN TIME: 15-30 minutes

PRESSING SCHEDULE: Approx. 4 bar (4 kg/sq cm) for 10-15 seconds.

➤ **CLEAN UP:**

Use Grasp ST71 (Styrene cleaner).

➤ **STORAGE & HANDLING:**

Avoid smoking and open flames. Is toxic by inhalation Provide good ventilation during work. Avoid contact with skin and eyes. Keep out of reach of Children.

➤ **PACKAGING:** 4 Ltr, 20 Ltr, 200 Ltr

The information presented is believed to be accurate, however, no guarantee is implied or given. User should conduct their own testing to determine the suitability of any product for a particular purpose.