

# NIGHTINGALE SUPPLY

PO BOX 712 HAMILTON CENTRAL 4007

PHONE: 3260.6544 FAX: 3260.6646

EMAIL: nightingale1@hotmail.net.au

## TECHNICAL DATA SHEET

# AG 90

### Acrylic Gap Sealant

➤ **DESCRIPTION:**

**AG 90 Gap Sealant** is a general purpose acrylic based sealant designed for weather proofing and joint sealing. It may be used as a flexible seal in masonry joints and cracks, and as a caulk around baths, shower screens and window frames.

➤ **SPECIFICATION:**

APPEARANCE:	WHITE THIXOTROPIC PASTE
SOLIDS:	APPROX. 80%
SPECIFIC GRAVITY:	APPROX. 1.6
SHELF LIFE:	UP TO 18 MONTHS STORED UNOPENED

➤ **DIRECTIONS FOR USE:**

May be applied to damp surfaces but all surfaces must be free of dust, grease, and loose matter. Use wet tools or fingers for tooling off.

Tack free in approx. ½ hour, fully cured in approx. 7 days. May be painted with water based paints immediately and with oil based paints after at least 2 days drying.

**NB: AG 90 Gap Sealant is not recommended for normal glazing applications.**

➤ **CLEAN UP:**

Use warm water on a cloth or sponge within 2 hours of application.

➤ **PACK SIZES: 300 ml. Cartridge (20 X 300 ML CARTON)**

The information presented is believed to be accurate, however, no guarantee is implied or given. User should conduct their own testing to determine the suitability of any product for a particular purpose.